

South Berwick Veterinary Hospital)	Departmental
York County)	Findings of Fact and Order
South Berwick, ME)	Air Emission License
A-142-71-E-R)	After-the-Fact

After review of the air emission license renewal application, staff investigation reports, and other documents in the applicant's file in the Bureau of Air Quality, pursuant to 38 M.R.S.A., Section 344 and Section 590, the Department finds the following facts:

I. REGISTRATION

A. Introduction

South Berwick Veterinary Hospital (SBVH) has applied to renew their Air Emission License, permitting the operation of a Class IV-A veterinary incinerator, to dispose of animal remains.

B. Equipment to be Licensed

The incinerator is a Shenandoah Model P25-2G with the following specifications:

Class Incinerator	IV-A
No. of Chambers	2
Type of Waste	Type 4
Max. Design Feed Rate	500 lb/load
Max. Design Combustion Rate	120 lb/hr
Auxiliary Fuel Input:	
Primary Chamber (Btu/hr)	319,000 LP Gas
Secondary Chamber (Btu/hr)	800,000 LP Gas
Emission Control	Afterburner

The incinerator combustion gases vent to an 18 foot AGL (Above Ground Level) stack. This represents 60% of the formula GEP (Good Engineering Practice) stack height based on the 12 foot AGL height of the inclined roof.

C. Application Classification

The last license for SBVH has lapsed, however, this application is treated as a renewal of an existing source. This application does not include the licensing of increased emissions or the installation of new or modified equipment.

BEST PRACTICAL TREATMENT

In order to receive a license, the applicant must control emissions from each unit to a level considered by the Department to represent Best Practical Treatment (BPT) , as defined in Chapter 100 of the Air Regulations.

BPT for existing equipment means that method which controls or reduces emissions to the lowest possible level considering:

- the existing state of technology;
- the effectiveness of available alternatives for reducing emissions from the source being considered; and
- the economic feasibility for the type of establishment involved.

This source was previously subject to Best Available Control Technology (BACT) requirements. The former BACT determination is now considered Best Practical Treatment for this source. BPT for the Class IV-A veterinary incinerator includes the following:

Temperatures in the secondary chamber shall be at least 1600°F with a stack gas retention time of at least 0.5 seconds. A prototype test report indicated that the average retention time in the secondary chamber was 0.5 seconds. A pyrometer will be installed and maintained at that location which will provide sufficient volume to ensure a retention time of at least 0.5 seconds at 1600°F in the secondary chamber.

To ensure an efficient burn and to prevent odors and visible emissions, the secondary chamber shall be preheated, as specified by the manufacturer, until the pyrometer temperature measures a minimum of 1600°F prior to commencing the burn cycle. The temperature shall remain at a minimum of 1600°F throughout the duration of the burn cycle.

A log will be maintained recording the weight of the waste charged, preheat time, charging time and the temperature of the secondary chamber every 60 minutes after start-up until, and including, final shutdown time. For facilities operating a chart recorder, the start time, date, and weight charged may be logged on the chart.

South Berwick Veterinary Hospital
York County
South Berwick, Maine
A-142-71-E-R

)
)
)
3

**Departmental
Findings of Fact and Order
Air Emission License
After-the-Fact**

A maximum particulate emission rate of 0.20 gr/dscf corrected to 12% CO₂ will be met. Prototype testing for this unit demonstrated an average particulate matter emission rate of 0.074 gr/dscf corrected to 12% CO₂.

Visible emissions from the incinerator shall not exceed 10% opacity based on a six (6) minute block average basis.

The ash will be disposed of in accordance with the requirements of the Bureau of Remediation and Waste Management.

The incinerator operator(s) shall receive adequate training to operate the incinerator in accordance with the manufacturer's specifications and shall be familiar with the terms of the Air Emission License.

Though it is not being required now, the installation and operation of continuous chart recording devices may become necessary to document compliance with the temperature requirements of this license.

III. AIR QUALITY ANALYSIS

According to Chapter 115 of the Maine Bureau of Air Quality Regulations, the level of air quality analysis and monitoring are determined on a case-by-case basis. Based on analysis for similar sources, the size of the source, the allowable emissions, the location, and the stack height, ambient air quality standards, including increments, are not expected to be violated. Therefore, an ambient air impact analysis will not be required for this source at this time.

ORDER

Based on the above Findings and subject to conditions listed below the Department concludes that the emissions from this above source:

- will receive Best Practical Treatment,
- will not violate applicable emission standards
- will not violate applicable ambient air quality standards in conjunction with emissions from other sources.

The Department hereby grants Air Emission License A-142-71-E-R, subject to the following conditions:

- (1) Employees and authorized representatives of the Department shall be allowed access to the licensee's premises during business hours, or any time which any emission units are in operation, and at such other times as the Department deems necessary for the purpose of

- performing tests, collecting samples, conducting inspections, or examining and copying records relating to emissions.
- (2) The licensee shall acquire a new or amended air emission license prior to commencing construction of a modification, unless specifically provided for in Chapter 115.
 - (3) Approval to construct shall become invalid if the source has not commenced construction within eighteen (18) months after receipt of such approval or if construction is discontinued for a period of eighteen (18) months or more. The Department may extend this time period upon a satisfactory showing that an extension is justified, but may condition such extension upon a review of either the control technology analysis or the ambient air quality standards analysis, or both.
 - (4) The licensee shall establish and maintain a continuing program of best management practices for suppression of fugitive particulate matter during any period of construction, reconstruction, or operation which may result in fugitive dust, and shall submit a description of the program to the Department upon request.
 - (5) The licensee shall pay the annual air emission license fee to the Department, calculated pursuant to Title 38 MRSA §353.
 - (6) The license does not convey any property rights of any sort, or any exclusive privilege.
 - (7) The licensee shall maintain and operate all emission units and air pollution control systems required by the air emission license in a manner consistent with good air pollution control practices for minimizing emissions.
 - (8) The licensee shall maintain sufficient records, to accurately document compliance with emission standards and license conditions and shall maintain such records for a minimum of six (6) years. The records shall be submitted to the Department upon written request.
 - (9) The licensee shall comply with all terms and conditions of the air emission license. The filing of an appeal by the licensee, the notification of planned changes or anticipated noncompliance by the licensee, or the filing of an application by the licensee for the renewal of a license or amendment shall not stay any condition of the license.
 - (10) The licensee may not use as a defense is an enforcement action that the disruption, cessation, or reduction of licensed operations would have been necessary to maintain compliance with the conditions of the air emission license.
 - (11) In accordance with the Department's air emission compliance test protocol and 40 CFR Part 60 or other method approved or required by the Department, the licensee shall:

- a. perform stack testing to demonstrate compliance with the applicable emission standards under circumstances representative of the facility's normal process and operating conditions:
 1. within sixty (60) calendar days of receipt of a notification to test from the Department or EPA, if visible emissions, equipment operating parameters, staff inspection, air monitoring or other cause indicate to the Department that equipment may be operating out of compliance with emission standards or license conditions;
or
 2. pursuant to any other requirement of this license to perform stack testing.
 - b. install or make provisions to install test ports that meet the criteria of 40 CFR part 60, Appendix A, and test platforms, if necessary, and other accommodations necessary to allow emission testing; and
 - c. submit a written report to the Department within thirty (30) days from the date of test completion.
- (12) If the results of a stack test performed under circumstances representative of the facility's normal process and operating conditions indicate emissions in excess and operating conditions indicate emissions in excess of the applicable standards, then:
- a. within thirty (30) days following receipt of such test results, the licensee shall re-test the non-complying emission source under circumstances representative of the facility's normal process and operating conditions and in accordance with the Department's air emission compliance test protocol and 40 CFR Part 60 or other method approved or required by the Department; and
 - b. The days of violation shall be presumed to include the date of stack test and each and every day of operation thereafter until compliance is demonstrated under normal and representative process and operating conditions, except to the extent that the facility can prove to the satisfaction that there were intervening days during which no violation occurred or that the violation was not continuing in nature; and
 - c. The licensee may, upon the approval of the Department following the successful demonstration of compliance at alternative load conditions, operate under such alternative load conditions on an interim basis prior to a demonstration of compliance under normal and representative process and operating conditions.
- (13) Notwithstanding any other provision in the State Implementation Plan approved by the EPA or Section 114(a) of the CAA, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any statute, regulation, or Part 70 license requirement.
- (14) The licensee shall maintain records of malfunctions, failures, downtime, and any other similar change in operation of air pollution control systems or the emissions unit itself that would affect emissions and that is not consistent with the terms and conditions of the air emission license. The licensee shall notify the Department within two (2) days or the next state working day, whichever is later, of such occasions when such changes result in an

- increase of emissions. The licensee shall report all excess emissions in the units of the applicable emission limitations.
- (15) Upon the written request of the Department, the licensee shall establish and maintain such records, make such reports, install, use, and maintain such monitoring equipment, sample such emissions (in accordance with such methods, at such locations, at such intervals, and in such a manner as the Department shall prescribe), and provide other information as the Department may reasonably require to determine the licensee's compliance data.
 - (16) The incinerator shall be used for the disposal of type 4 (veterinary) waste and shall not be used for the disposal of plastics, cytotoxic (antineoplastic) drugs or any radioactive wastes and shall not be used to dispose of any medical waste classified as type 7 waste, as defined in Maine Air Regulations Chapter 100.
 - (17) The incinerator shall not exceed the maximum design feed rate of 500 lb/load and combustion rate of 120 lbs per hour, respectively. Auxiliary fuel input to the primary and secondary chamber shall not exceed 319,000 btu/hr, and 800,000 btu/hr respectively of LP gas.
 - (18) A log shall be maintained recording the weight of waste charged, preheating time, charging time, afterburner temperature directly after charging and every 60 minutes after startup until, and including, final shutdown time. For facilities operating a chart recorder, the start time, date, and weight of waste charged may be logged on the chart.
 - (19) The secondary chamber shall be preheated as specified by the manufacturer to a minimum of 1600⁰F prior to combusting any waste and shall be maintained at a minimum of 1600⁰F during the duration of the burn.
 - (20) Once the burn cycle has commenced by introduction of primary chamber combustion, the incinerator shall be operated in an efficient manner and as specified by the manufacturer for the period of time between preheat and reaching the set operational temperature to be a minimum of 1600⁰F in the secondary chamber.
 - (21) A pyrometer and ¼ inch test port shall be installed and maintained at that location of the incinerator or refractory lined stack which provides sufficient volume to insure a flue gas retention time of not less than 0.5 seconds at the minimum of 1600⁰F.
 - (22) SBVH shall not exceed a particulate matter emission limit of 0.20 gr/dscf corrected to 12% CO₂ from the auxiliary fuel. Therefore, based on the maximum design combustion rate and continuous operation of the Class IV-A incinerator, emissions shall be limited to the following:

South Berwick Veterinary Hospital
York County
South Berwick, Maine
A-142-71-E-R

)
)
)
7

Departmental
Findings of Fact and Order
Air Emission License
After-the-Fact

<u>Pollutant</u>	<u>gr/dscf</u>	<u>lb/hr</u>	<u>TPY</u>
PM	0.20	0.13	0.44
PM ₁₀	0.20	0.13	0.44
SO ₂	-	0.06	0.22
NO _x	-	0.26	0.88
CO	-	0.08	0.26
VOC	-	0.01	0.04

- (23) Visible emissions from the incinerator shall not exceed an opacity limit of 10% based on a six-minute block average basis.
- (24) The incinerator combustion gases shall vent to a stack of at least 18 feet AGL.
- (25) The ash will be disposed of in accordance with the requirements of the Bureau of Remediation and Waste Management.
- (26) The incinerator operator(s) shall receive adequate training to operate the incinerator in accordance with the manufacturer's specifications, and shall be familiar with the terms of this Air Emission as it pertains to the operation of the incinerator.
- (27) Though it is not being required now, the installation and operation of continuous chart recording devices may become necessary to document compliance with the temperature requirements of this license. Should the Bureau of Air Quality determine that continuous recording devices are necessary, the licensee shall, within 120 days, demonstrate that continuous recorders have been installed and are operational.

South Berwick Veterinary Hospital
York County
South Berwick, Maine
A-142-71-E-R

)
)
)
8

Departmental
Findings of Fact and Order
Air Emission License
After-the-Fact

(28) The term of this order shall be for five (5) years from the date of signature.

DONE AND DATED IN AUGUSTA, MAINE THIS DAY OF 2000.

DEPARTMENT OF ENVIRONMENTAL PROTECTION

BY: _____
MARTHA G. KIRKPATRICK, COMMISSIONER

PLEASE NOTE THE ATTACHED SHEET FOR GUIDANCE ON APPEAL PROCEDURES

Date of initial receipt of application: December 6, 1999

Date of application acceptance: December 28, 1999

Date filed with the Board of Environmental Protection _____

This Order prepared by Elisha McVay, Bureau of Air Quality.